

Why you should go with Industrial Oil Skimmers



Why fenton oil skimmers

- The Unique Method of Oil Removal
- Easy To Operate
- Antirust Coated Body
- Pickup Oils Not Water
- Long Lasting / Low Maintenance
- Ease Of Installation
- Manufactured By reliable and Reputed Company
- Power Saving And Energy Efficient benefits
- Heavy duty Skimmer



Innovative Design



Less Footprint



Ease of use



Plug & Play



Less Maintenance



FENTON Service Benefits



Onsite Warranty*

MODEL	FENTON - MINI	FENTON - MASTER
OIL REMOVAL RATE	0-40 LPH	0-60 LPH
DESIGN	Design with High Durable Material	Design with High Durable Material
TAIL PULLEY	Innovative Compact Type	As Per Industrial standard
MOTOR	220 V Single Phase 950/1440 RPM	415 V Three Phase 950/1440 RPM
BELT WIDTH	4 inch	4 inch & 6 Inch
BELT LENGTH	3 meter (1.5 meter measured from the centre of head pulley to centre of tail pulley)	3 (1.5 measured from the centre of head pulley to centre of tail pulley) available upto 10 meter
BELT MATERIAL	PU /PVC/SS	PU /PVC/SS
WIPER	Nitrile / Tafelon standard; CRV optional. Specify wiper material based on temperature and uid compatibility. (See "Operating Limits.")	Nitrile / Tafelon standard; CRV optional. Specify wiper material based on temperature and uid compatibility. (See "Operating Limits.")
MOUNTING METHOD	See installation drawing.	See installation drawing.
WEIGHTS	Complete assembly with Heavy Motor, tail pulley, and belt: 20 kg Aproximate (Note: optional hose w/clamp and adapter weight 1 kg)	Complete assembly with Motor, tail pulley, and belt: 30 kg (Note: optional hose w/clamp and adapter weight 1 kg)
	Options Specify	Options Specify
OPTIONS SPECIFY	Flat surface mount kit Tail pulley cage and tether assembly for operation in turbulent liquids. oil discharge pipe kit along with Oil Tray Floor mounted support stand. Anti Rust Powder coated protection for outside applications Timer and electrical controls	Flat surface mount kit Tail pulley cage and tether assembly for operation in turbulent liquids. 1.5" oil discharge pipe kit Floor mounted support stand. Powder coated protection for outside applications Timer and electrical controls

